

(51) International Patent Classification ⁵ : A61M 5/50 // 5/32		A1	(11) International Publication Number: WO 94/23778
			(43) International Publication Date: 27 October 1994 (27.10.94)
(21) International Application Number: PCT/SE94/00353		(81) Designated States: AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, ES, FI, GB, GE, HU, JP, KG, KP, KR, KZ, LK, LU, LV, MD, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SI, SK, TJ, TT, UA, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 20 April 1994 (20.04.94)			
(30) Priority Data: 9301291-2 20 April 1993 (20.04.93) SE			
(71)(72) Applicant and Inventor: LEIJU, Nicklas [SE/SE]; Svartbäcksgården 649, S-136 59 Haninge (SE).		Published With international search report. In English translation (filed in Swedish).	
(74) Agents: BROLIN, Tommy et al.; Brolin & Sedvall Patentbyrå AB, P.O. Box 7182, S-103 88 Stockholm (SE).			

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LV	Luxembourg	SN	Senegal
CN	China	LU	Lithuania	TD	Chad
CS	Czechoslovakia	LV	Lithuania	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

CANNULA WITH PROTECTIVE DEVICE

5 The present invention relates to a cannula having an automatically activated protective device (protective capsule) intended for the injection needle of the cannula or hypodermic syringe. The protective device has the form of a hollow cylinder provided with two bottoms which include two central cavities, and includes an internally mounted latching and a locking system which functions to
10 apply the protective device automatically to the forward pointed part of the injection needle when the needle is retracted or withdrawn manually so as to separate the needle from the cannula chassis. The protective device is arranged internally in the cannula chassis in a fixed
15 position, and is released from this fixed position by means of an appropriate retroaxial pulling force, and accompanies the needle applied thereto as a protective capsule which encapsulates the point of the injection needle as the needle is separated from the chassis. The encapsulated
20 point of the injection needle eliminates the risk of infection by "unfortunate pricking" with used, infected injection needles. The risk entailed by reusing the injection needle is eliminated, since the needle is deformed upon activation of the latching and locking
25 process.

Those cannula or hypodermic syringes at present available commercially constitute a risk as a result of their construction and design, this risk being particularly
30 applicable to nursing personnel who during their work are liable to "unfortunately prick themselves" with used, infected injection needles, with extremely serious consequences.

35 The irresponsible reuse of injection needles can occur. The described invention eliminates the above-mentioned risks.

OBJECT OF THE INVENTION AND ITS MAIN CHARACTERISTIC FEATURES

5 The object of the invention is to provide for the comfort and, primarily, the safety of those who handle cannula or hypodermic syringes and to render irresponsible reuse of infected injection needles impossible. The object is to provide a cannula with a protective device on the point of the injection needle. The protective device is mounted
10 internally of the cannula chassis, in a fixed position, and can be released from this fixed position by means of an appropriate retroaxial pulling force, wherewith the protective device accompanies this movement while seated on the front part of the injection needle, where the protective device is locked firmly to the point of the injection
15 needle by latching and locking means as the injection needle is separated from the cannula chassis. The invention thus relates to a cannula intended for one-time use only, since the cannula - the injection needle - is deformed upon
20 activation of the latching and locking mechanism. The invention is activated by means of cooperation between retroaxial displacement of the injection needle - perforations provided at the front part of the injection needle, the point - where latching flaps provided internally of the
25 protective device hook firmly when the latching and locking mechanism is activated, resulting in secure and stable encapsulation of the front part, the point, of the injection needle by the protective device.

30 The invention will now be described in more detail with reference to an exemplifying embodiment thereof and also with reference to the accompanying drawings, in which

35 - Fig. 1A is a schematic, longitudinal section view of a first embodiment of an inventive cannula provided with a protective device;

- Fig. 1B is a schematic, longitudinal section view of a second exemplifying embodiment of an inventive cannula provided with a protective device;
- 5 - Fig. 2A is a schematic illustration of one part of a cannula having a protective device in said first embodiment of the invention;
- Fig. 2B is a schematic, longitudinal section view of a
10 cannula provided with a protective device according to the first embodiment of the invention, and shows the latching and locking mechanism activated;
- Fig. 3A illustrates schematically part of the cannula
15 provided with a protective device according to the second embodiment of the invention;
- Fig. 3B is a schematic, longitudinal section view of a
20 cannula provided with a protective device in accordance with the second embodiment of the invention, with the latching and locking mechanism activated;
- Fig. 4 illustrates schematically a plurality of axially
25 and radially separated perforations provided at the front part, the point, of the injection needle;
- Fig. 5 is a schematic, longitudinal section view of the
cannula having an internally arranged protective device
30 according to the first embodiment of the invention, and shows the protective device in three different positions; in which
- Fig. 5A shows the cannula and protective device disposed,
35 in a fixed appropriate position;

- Fig. 5B shows the cannula and protective device with the cannula injection needle retracted axially, and shows internal latching and locking system activated;
- 5 - Fig. 5C illustrates the cannula with the protective device separated from the cannula. Flexible inlet or outlet tubes are provided in the "rear cap" of the cannula, the cannula is prepared for the intended function; and
- 10 - Fig. 6 is a schematic, longitudinal section view of the cannula and protective device according to a third embodiment of the invention.

15 The reference numeral 1 identifies part of the cannula in which the injection needle can be moved and the purpose of which is to perforate the body and permit the body to be penetrated by a flexible plastic tube 13, which is provided at the outer circumference of the injection needle 1 so as to leave solely the point protruding and free. The injection needle 1 provides adequate support, stability, to the flexible plastic tube 13 for penetration thereof into the body.

25 The reference numeral 2 identifies the chassis of a protective device adjacent the injection needle 1, which is in the form of a hollow cylinder having two bottoms provided with a centrally located hollow cavity 6, and internally mounted latching and locking system for applying the protective device to the front part, the point, of the injection needle 1 (chassis 2 is manufactured in two different units for technical reasons, these two units being joined together, although this is not shown in the drawings).

35 The reference numeral 3 identifies support flanges provided internally in the chassis 2, the purpose of which is to centralize the injection needle 1 and to provide adequate

support when the injection needle 1 is deformed upon activation of a latching flap 4 (Fig. 2B 41).

5 The reference numeral 4 identifies latching flaps provided internally in the chassis 2 and intended to permit forward displacement of the injection needle 1 (see Fig. 2A), but to activate a latching and locking system when the injection needle 1 is retracted manually in an axial direction, such that the latching flap 4 will hook firmly to a
10 vertical surface 9' which is present on the forward part of the injection needle 1. An active latching and locking process results in deformation and locking of the injection needle 1 in a fixed position at the chassis 2 of the protective device (see Fig. 2B).

15 The reference numeral 5 identifies a position fixing ring which is provided on the outer circumference of the chassis 2 and by means of which the protective device is guaranteed an appropriate position internally of the cannula.

20 The reference numeral 6 identifies two centrally located cavities at the two hollow cylindrical bottoms of the chassis 2 by means of which the injection needle 1 is stabilized and centralized.

25 The reference numeral 7 identifies the chassis of the protective device at the injection needle 1 in accordance with the second embodiment of the invention (for technical reasons, the chassis 7 has been manufactured in two
30 different units which are later joined together, although this is not shown in the drawings).

35 The reference numeral 8 identifies a support flange internally of a part of the chassis 7, wherein the support flange 8 coacts with the latching flap 4 in deforming and locking the injection needle 1 (see Fig. 3B).

The reference numeral 9 identifies a plurality of axially and radially separated perforations located on the outer circumference of the front part of the injection needle 1. The triangular perforations 9 are intended to allow the injection needle to move forwards, but when the injection needle 1 is withdrawn axially and the perforations 9 reach the action radius of the latching flap 4, the flap is activated and hooks firmly onto the vertical perforated surface 9' located at the outer circumference of the front part of the injection needle 1. By means of coaction - cannula - axial retraction or withdrawal of the injection needle 1 plus the perforations 9 plus latching flap 4, the latching and locking system of the protective device is activated and the injection needle 1 is deformed and locked firmly in a fixed position (see Fig. 2B).

The reference numeral 10 identifies a concave circular space located internally of the cannula, the purpose of said space being to fix the chassis 2 and 7 in an appropriately fixed position in the cylindrical internal space 12 of the cannula.

The reference numeral 11 identifies the cannula chassis.

The reference numeral 12 identifies the cylindrical internal space present in the cannula.

The reference numeral 13 identifies a flexible plastic tube applied to the cannula chassis 11.

The reference numeral 14 identifies a cap appendage firmly fixed to the rear part of the injection needle 1, the cap appendage 14 being transparent to permit the arrival of blood to be visually discerned.

The reference numeral 15 identifies a cap provided on the rear part of the cannula chassis 11.

The reference numeral 16 identifies a space formed at the cap appendage 14, to enable the arrival of blood to be visually discerned.

5 The reference numeral 17 identifies a hollow space formed centrally adjacent the cap 15, the purpose of this space being intended to facilitate the application of a flexible plastic tube 151 through which liquid is introduced or removed.

10 The reference numeral 18 identifies a formed space present internally in the cannula.

15 The reference numeral 19 identifies the chassis of the protective device adjacent the injection needle 1, according to a third embodiment of the invention. The chassis 19 has a hollow cylindrical shape with two bottoms having centrally located hollow cavities 6, and an internal latching and locking system is provided for putting the
20 protective device onto the front part, the point, of the injection needle 1. The lower hollow cylindrical bottom of the chassis 19 has the form of a truncated cone and is force-fitted into the circular plate 20 which has corresponding inclination (see Fig. 6, 21) and the chassis has
25 only adequate axial withdrawal effect to release the chassis 19 from the internal circular plate 20 fixedly mounted in the front part of the cannula. The internally mounted latching and locking system of the chassis is activated first by means of manual retro-movement of the
30 injection needle 1 when the chassis 19 is locked firmly in a fixed position at the front part of the injection needle 1 as a protective capsule, whereas continued appropriate manual retroaxial pulling force will cause the separating process of the fixing device to function and the point of
35 the injection needle 1 encapsulated by the chassis 19 is separated from the cannula chassis 11. (See Figs. 5A, B, C). The third embodiment of the invention is mainly

characterized in that the protective device is provided internally with an adhesive substance at the forward frontal area of the cannula chassis 11 and is thus not dependent on the external dimension, nor yet on any particular fixating system.

The reference numeral 20 identifies a circular part which is fixedly mounted to the forward frontal area of the cannula chassis 11 by means of an adhesive. The part 20 having an internal circular inclination 21 for its application to the front part of the chassis 19 where a similar inclination is found. The part 20 may also be applied in an appropriate position by means of a fixating system 201 provided internally in the cannula chassis 11.

The reference numeral 21 identifies a similar inclination on the front part of the chassis 19 and internally of the part 20.

The reference numeral 22 identifies the planar surface present on the circular part 20 with existing glue or paste to enable adhesive application of the protective device at the forward frontal area of the cannula chassis 11.

CLAIMS

1. A cannula comprising internally in a fixed position in the front part of the cannula chassis (11) an automatically functioning protective device (protective capsule) for the point of the cannula injection needle, said protective device having a hollow cylindrical construction and including two bottoms each having a respective hollow space (6) and including internally a latching and locking system which by application of the protective device protectively encapsulates the injection needle (1) during the process of separating the needle from the cannula, characterized in that the protective device includes internally radially functioning latching flaps (4) which are constructed to permit forward movement of the injection needle (1) but which when the needle (1) is retracted manually hook firmly to a vertical surface (9') forming part of perforations (9) on the front part of the needle (1), so that the needle (1) will be deformed and locked firmly in a fixed position in the protective device, which accompanies the needle (1) as the needle is separated from the cannula chassis (11).

2. A cannula according to Claim 1, characterized by a plurality of axially and radially separate perforations (9) provided on the front part of the injection needle (1), wherein the purpose of said perforations is to permit forward movement of the injection needle (1), wherein when the injection needle (1) is retracted or withdrawn axially and the perforations (9) reach the action radius of the radially acting latching flap (4), the latching and locking system located internally in the cannula protective device is automatically activated.

3. A cannula according to Claim 1, 2, characterized in that the internally arranged cannula protective device is disparate, and the injection needle (1) is bent axially and deformed (see Fig. 3).

10

4. A cannula according to Claim 1, 2, 3, characterized in that the protective device of the cannula is disparate in construction, the lower bottom, the front part, has the shape of a truncated cone onto which there is force-fitted
5 a circular subpart (20) having internally a similar inclination, the subpart (20) having a planar surface (22) on which glue or paste is applied to enable the protective device to be applied adhesively to the inner forward frontal area of the cannula chassis (11). The cannula
10 chassis (19) and the subpart (20) are separated by applying an appropriate retroaxial pulling force. The third embodiment of the invention is mainly characterized in that when the protective device is adhered to the inner forward frontal area of the cannula chassis (11), the protective
15 device is not dependent on precise dimensions nor on a separate fixating system.

1 / 5

Fig. 1A





Fig. 1B



SUBSTITUTE SHEET

2 / 5

Fig. 2A






Fig. 2B



A-A

SUBSTITUTE SHEET

3 / 5

Fig. 3A







Fig. 3B






SUBSTITUTE SHEET

4 / 5

Fig. 5A

Fig. 5B

Fig. 5C



SUBSTITUTE SHEET

5 / 5

Fig. 4





Fig. 6



SUBSTITUTE SHEET

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 94/00353

A. CLASSIFICATION OF SUBJECT MATTER

IPC5: A61M 5/50 // A61M 5/32

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC5: A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US, A, 5015234 (ROBERT G. JULLIEN), 14 May 1991 (14.05.91), figure 2d, abstract -----	1-4

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

19 July 1994

Date of mailing of the international search report

28 -07- 1994

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

May Hallne
Telephone No. +46 8 782 25 00

02/07/94

PCT/SE 94/00353

Form PCT/ISA/210 (patent family annex) (July 1992)

THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)